


C1 series package: 1700V 150A IGBT module**Datasheet**

Equivalent
Circuit Schematic

Features:

- Trenchgate Gen.7 IGBT technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High RBSOA capability
- Low static losses: $V_{CE(sat)} = 1,6V@25C$
- Low dynamic losses

Options:

- Pre-applied TIM
(option +M01)

Typical Applications:

- Motor Drives
- Uninterrupted Power Supply
- Photovoltaic

**IGBT, Inverter / IGBT
Maximum Rated Values**

Collector-emitter Voltage	$T_{vj} = 25^{\circ}\text{C}$	V_{CES}	1700	V
Continuous DC Collector Current		I_{Cnom}	150	A
	$T_C = 100^{\circ}\text{C}, T_{vj\ max} = 175^{\circ}\text{C}$	I_C	180	A
Repetitive Peak Collector Current	$I_{CRM} = 2 \times I_{Cnom}$	I_{CRM}	300	A
Total power dissipation	$T_C = 25^{\circ}\text{C}, T_{vj\ max} = 175^{\circ}\text{C}$	P_{tot}	830	A
Gate-emitter Peak Voltage		V_{GES}	± 20	V

Characteristic Values

			min.	typ.	max.	
Collector-emitter Saturation Voltage ¹⁾	$I_C = 150\text{A}, V_{GE} = 15\text{V}$ $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	V_{CEsat}		1.60 1.73 1.77 1.82		V
Gate Threshold Voltage	$V_{CE} = V_{GE}, I_C = 3\text{mA}, T_{vj} = 25^{\circ}\text{C}$	V_{GEth}	5.50	6.10	6.70	V
Gate Charge	$V_{GE} = -8\text{V}/15\text{V}, V_{CE} = 900\text{V}, T_{vj} = 25^{\circ}\text{C}$	Q_G	—	1.33	—	μC
Internal Gate Resistor	$T_{vj} = 25^{\circ}\text{C}$	R_{Gint}	—	1.6	—	Ω
Input Capacitance	$V_{CE} = 25\text{V}, V_{GE} = 0\text{V}$ $f = 100\text{kHz}, T_{vj} = 25^{\circ}\text{C}$	C_{ies}	—	34.2	—	nF
Reverse Transfer Capacitance		C_{res}	—	0.10	—	nF
Collector-emitter Cutoff Current	$V_{CE} = 1700\text{V}, V_{GE} = 0\text{V}, T_{vj} = 25^{\circ}\text{C}$	I_{CES}	—	—	1	μA
Gate-emitter Leakage Current	$V_{CE} = 0\text{V}, V_{GE} = 20\text{V}, T_{vj} = 25^{\circ}\text{C}$	I_{GES}	—	—	200	nA
Turn-on Delay Time, Inductive Load	$I_C = 150\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{gon} = 4\Omega$ $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_{don}	—	125 125 130 135	—	ns
Rise Time, Inductive Load	$I_C = 150\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{gon} = 4.0\Omega$ $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_r	—	45 55 55 60	—	ns
Turn-off Delay Time, Inductive Load	$I_C = 150\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{Goff} = 4.0\Omega$ $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_{doff}	—	370 430 445 460	—	ns
Fall Time, Inductive Load	$I_C = 150\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{Goff} = 4.0\Omega$ $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_f	—	295 585 680 780	—	ns
Turn-on Energy Loss per Pulse	$I_C = 150\text{A}, V_{CE} = 900\text{V},$ $L_{\sigma} = 28\text{nH}, V_{GE} = \pm 15\text{V},$ $R_{Gon} = 4.0\Omega,$ $di/dt = 2000\text{ A}/\mu\text{s} (T_{vj} = 175^{\circ}\text{C})$ $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	E_{on}	—	25.5 32.0 34.5 36.0	—	mJ
Turn-off energy Loss per Pulse	$I_C = 150\text{A}, V_{CE} = 900\text{V},$ $L_{\sigma} = 28\text{nH}, V_{GE} = \pm 15\text{V},$ $R_{Goff} = 4.0\Omega$ $dv/dt = 3900\text{ V}/\mu\text{s} (T_{vj} = 175^{\circ}\text{C})$ $T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	E_{off}	—	26.0 45.0 50.0 55.0	—	mJ

1) Terminal impedance is not included.

SC Data	VCE = 1000 V VGE = ±15 V	tp ≤ 8us, Tvj = 150°C	ISC		680		A
		tp ≤ 6us, Tvj = 175°C			650		
Thermal Resistance, Junction to Case	Per IGBT		RthJC	—	0.180	—	K/W
Temperature under Switching Conditions ²⁾			Tvj op	-40		175	°C

Diode, Inverter Maximum Rated Values

Repetitive Peak Reverse Voltage	Tvj = 25°C	VRRM	1700	V
Continuous DC Forward Current		IF	150	A
Repetitive Peak Forward Current	ICRM = 2 x Ifnom	IFRM	300	A

Characteristic Values

			min.	typ.	max.	
Forward Voltage ¹⁾	IF = 150A, VGE = 0V	Tvj = 25°C Tvj = 125°C Tvj = 150°C Tvj = 175°C	VF		1.57 1.67 1.67 1.66	2.40 V
Peak Reverse Recovery Current	IF = 150A, VR = 900V -diF/dt = 3700A/us (Tvj = 175°C) VGE = -15V	Tvj = 25°C Tvj = 125°C Tvj = 150°C Tvj = 175°C	IRM	—	225 230 235 240	— A
Recovery Charge	IF = 150A, VR = 900V -diF/dt = 3700A/us (Tvj = 175°C) VGE = -15V	Tvj = 25°C Tvj = 125°C Tvj = 150°C Tvj = 175°C	QR	—	19.5 24.0 27.5 28.5	— uC
Reverse Recovery Energy	IF = 150A, VR = 900V -diF/dt = 3700A/us (Tvj = 175°C) VGE = -15V	Tvj = 25°C Tvj = 125°C Tvj = 150°C Tvj = 175°C	Erec	—	9.10 16.0 17.0 17.5	— mJ
Thermal Resistance, Junction to Case	Per Doide		RthJC	—	0.238	— K/W
Temperature under Switching Conditions ²⁾			Tvj op	-40	—	175 °C

Module

Isolation Test Voltage	RMS, f = 50Hz, t = 1min	VISOL	3.0	kV
Material of Module Baseplate			Cu	
Internal Isolation	(class 1, IEC 61140) Basic insulation (class 1, IEC 61140)		AL2O3	
Creepage Distance	Terminal to heatsink Terminal to terminal		17.0 20.0	mm
Clearance	Terminal to heatsink Terminal to terminal		17.0 9.5	mm
Comparative Tracking Index		CTI	>200	


				min.	typ.	max.
Thermal resistance, case to heatsink	per module $\lambda_{\text{Paste}} = 1\text{W}/(\text{m}\cdot\text{K})/\lambda_{\text{grease}} = 1\text{W}/(\text{m}\cdot\text{K})$	R_{thCH}		0.05		K/W
Stray Inductance Module		L_{sCE}	—	30	—	nH
Module Lead Resistance, Terminals-Chip	$T_C = 25^\circ\text{C}$, Per Switch	$R_{\text{CC}'+\text{EE}'}$	—	0.65	—	m Ω
Storage Temperature		T_{stg}	-40	—	125	$^\circ\text{C}$
Modul MountingTorque	M6	M	4.0	—	6.0	Nm
Terminal MountingTorque	M5	M	3.0	—	6.0	Nm
Weight		G	—	145	—	g

1) Terminal impedance is not included.


2) $T_{vj\text{ op}} > 150^\circ\text{C}$ is only allowed for operation at overload conditions.

Circuit Diagram


Output characteristic IGBT, Inverter (typical), IGBT
 $I_c = f(V_{CE})$, $V_{GE} = 15V$




Output characteristic IGBT, Inverter (typical), IGBT
 $I_c = f(V_{CE})$, $T_{vj} = 175^{\circ}C$




Transfer characteristic IGBT, Inverter (typical), IGBT
 $I_c = f(V_{GE})$, $V_{CE} = 20V$




Switching losses IGBT, Inverter (Typical), IGBT
 $E_{on} = f(I_c)$, $E_{off} = f(I_c)$
 $V_{GE} = \pm 15V$, $R_{Gon} = 4\Omega$, $R_{Goff} = 4\Omega$, $V_{CE} = 900V$




Switching losses IGBT, Inverter (typical), IGBT
 $V_{GE} = \pm 15V$, $I_C = 150A$, $V_{CE} = 900V$




Transient thermal impedance IGBT, Inverter
 $Z_{thJC} = f(t)$




Switching time IGBT, Inverter (typical)
 $t = f(I_C)$
 $R_{goff} = 4.0\Omega$, $R_{gon} = 4.0\Omega$, $V_{CE} = 900V$, $V_{GE} = \pm 15V$, $T_{vj} = 175^\circ C$




Switching time IGBT, Inverter (typical)
 $t = f(R_g)$
 $I_C = 150A$, $V_{CE} = 900V$, $V_{GE} = \pm 15V$, $T_{vj} = 175^\circ C$




Reverse bias safe operating area IGBT, Inverter
(RBSOA) $I_C = f(V_{CE})$,
 $V_{GE} = \pm 15V$, $R_{Goff} = 4\Omega$, $T_{vj} = 175^\circ C$




Forward characteristic of Diode, Inverter (typical)
 $I_F = f(V_F)$



Gate charge characteristic, IGBT, Inverter (typical)
 $V_{GE} = f(Q_g)$
 $I_C = 150A$, $T_{vj} = 25^\circ C$




Capacity characteristic, IGBT, Inverter (typical)
 $C = f(V_{CE})$
 $f = 100kHz$, $V_{GE} = 0V$, $T_{vj} = 25^\circ C$



Switching losses Diode, Inverter (typical)

$$E_{rec} = f(I_F)$$


$$R_{Gon} = 4\Omega, V_{CE} = 900V$$



Switching losses Diode, Inverter (typical)


$$E_{rec} = f(R_G)$$

$$I_F = 150A, V_{CE} = 900V$$




Transient thermal impedance Diode , Inverter


$$Z_{thJC} = f(t)$$



Internal Circuit



Package Dimension Dimensions in Millimeters



Terms and Conditions of Usage

The data contained in this product datasheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application.

This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant the terms and conditions of the supply agreement. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary.

The user of Technicon products is responsible for the safety of their applications embedding Technicon products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of Technicon products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards.

Except as otherwise explicitly approved by Technicon in a written document signed by authorized representatives of Technicon, Technicon products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. Technicon does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others.

Technicon makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. This document supersedes and replaces all information previously supplied and may be superseded by updates. Technicon reserves the right to make changes.

For any questions or suggestions, please contact us at info@technicon.asia .