


C5 series package: 1700V 600A IGBT module

Equivalent
Circuit Schematic

Features:

- $V_{CES} = 1700V$
- $I_C \text{ nom} = 600A$
- Trenchgate Gen.7 IGBT technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High RBSOA capability
- Low static losses: $V_{CE(sat)} = 1,6V@25C$

Options:

- pre-applied TIM (option +M01)
- adoption for parallel connection (V_f selection)

Typical Applications:

- Motor Drives
- Solar Applications
- UPS Systems
- Energy Storage

**IGBT, Inverter / IGBT
Maximum Rated Values**

Collector-emitter Voltage	$T_{vj} = 25^{\circ}\text{C}$	V_{CES}	1700	V
Implemented Collector Current		I_{Cnom}	600	A
Continuous DC Collector Current	$T_C = 85^{\circ}\text{C}, T_{vj\ max} = 175^{\circ}\text{C}$	I_C	600	A
Repetitive Peak Collector Current	$t_p\ T_{vj\ op}$	I_{CRM}	1200	A
Gate-emitter Peak Voltage		V_{GES}	± 20	V

Characteristic Values
min. typ. max.

Collector-emitter Saturation Voltage ¹⁾	$I_C = 600\text{A}, V_{GE} = 15\text{V}$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	V_{CEsat}	-	1.60 1.78 1.86 1.90	-	V
Gate Threshold Voltage	$V_{CE} = V_{GE}, I_C = 12\text{mA}, T_{vj} = 25^{\circ}\text{C}$		V_{GEth}	5.6	6.20	6.80	V
Gate Charge	$V_{GE} = -10\text{V}/15\text{V}, V_{CE} = 900\text{V}$		Q_G	-	4.3	-	μC
Internal Gate Resistor	$T_{vj} = 25^{\circ}\text{C}$		R_{Gint}	-	0.46	-	Ω
Input Capacitance	$f = 100\text{kHz}, T_{vj} = 25^{\circ}\text{C}, V_{CE} = 25\text{V}, V_{GE} = 0\text{V}$		C_{ies}	-	102	-	nF
Reverse Transfer Capacitance	$f = 100\text{kHz}, T_{vj} = 25^{\circ}\text{C}, V_{CE} = 25\text{V}, V_{GE} = 0\text{V}$		C_{res}	-	0.27	-	nF
Collector-emitter Cutoff Current	$V_{CE} = 1700\text{V}, V_{GE} = 0\text{V}, T_{vj} = 25^{\circ}\text{C}$		I_{CES}	-	-	1	mA
Gate-emitter Leakage Current	$V_{CE} = 0\text{V}, V_{GE} = 20\text{V}, T_{vj} = 25^{\circ}\text{C}$		I_{GES}	-	-	100	nA
Turn-on Delay Time, Inductive Load	$I_C = 600\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{GON} = 1\Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_{don}	-	94 101 102 110	-	ns
Rise Time, Inductive Load	$I_C = 600\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{GON} = 1\Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_r	-	47 55 58 60	-	ns
Turn-off Delay Time, Inductive Load	$I_C = 600\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{Goff} = 1\Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_{doff}	-	394 470 490 500	-	ns
Fall Time, Inductive Load	$I_C = 600\text{A}, V_{CE} = 900\text{V}$ $V_{GE} = \pm 15\text{V}$ $R_{Goff} = 1\Omega$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	t_f	-	404 716 786 850	-	ns
Turn-on Energy Loss per Pulse	$I_C = 600\text{A}, V_{CE} = 900\text{V}, L_{\sigma} = 30\text{nH}$ $V_{GE} = \pm 15\text{V}, R_{GON} = 1\Omega$ $di/dt = 7800\text{ A}/\mu\text{s} (T_{vj} = 175^{\circ}\text{C})$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	E_{on}	-	97 132 142 165	-	mJ
Turn-off energy Loss per Pulse	$I_C = 600\text{A}, V_{CE} = 900\text{V}, L_{\sigma} = 30\text{nH}$ $V_{GE} = \pm 15\text{V}, R_{Goff} = 1\Omega$ $du/dt = 3800\text{ A}/\mu\text{s} (T_{vj} = 175^{\circ}\text{C})$	$T_{vj} = 25^{\circ}\text{C}$ $T_{vj} = 125^{\circ}\text{C}$ $T_{vj} = 150^{\circ}\text{C}$ $T_{vj} = 175^{\circ}\text{C}$	E_{off}	-	141 209 226 242	-	mJ
SC Data	$V_{GE} \leq 15\text{V}$ $V_{CC} = 1000\text{V}$ $V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$	$t_p \leq 10\mu\text{s}, T_{vj} = 25^{\circ}\text{C}$ $t_p \leq 6\mu\text{s}, T_{vj} = 175^{\circ}\text{C}$	I_{sc}	-	3000 2400	-	A

Thermal Resistance, Junction to Case	Per IGBT	R _{thJC}	-	0.049	-	K/W
Thermal Resistance, Case to Heatsink	Per IGBT $\lambda_{grease} = 1W/(m \cdot K)$	R _{thCH}	-	0.033	-	K/W
Temperature under Switching Conditions ²⁾		T _{vj op}	-40		175	°C

Diode, Inverter Maximum Rated Values

Repetitive Peak Reverse Voltage	T _{vj} = 25°C	V _{RRM}		1700		V
Continuous DC Forward Current		I _{Fnom}		600		A
Repetitive Peak Forward Current	t _p = 1ms	I _{FRM}		1200		A

Characteristic Values

				min.	typ.	max.	
Forward Voltage ¹⁾	I _F = 600A, V _{GE} = 0V	T _{vj} = 25°C T _{vj} = 125°C T _{vj} = 150°C T _{vj} = 175°C	V _F	-	1.65 1.83 1.82 1.80	-	V
Peak Reverse Recovery Current	I _F = 600A, V _R = 900V -di _F /dt = 10300 A/us (T _{vj} = 175°C) V _{GE} = -15V	T _{vj} = 25°C T _{vj} = 125°C T _{vj} = 150°C T _{vj} = 175°C	I _{RM}	-	808 816 808 760	-	A
Recovery Charge	I _F = 600A, V _R = 900V -di _F /dt = 10300 A/us (T _{vj} = 175°C) V _{GE} = -15V	T _{vj} = 25°C T _{vj} = 125°C T _{vj} = 150°C T _{vj} = 175°C	Q _R	-	86 107 111 119	-	μC
Reverse Recovery Energy	I _F = 600A, V _R = 900V -di _F /dt = 10300 A/us (T _{vj} = 175°C) V _{GE} = -8V	T _{vj} = 25°C T _{vj} = 125°C T _{vj} = 150°C T _{vj} = 175°C	E _{rec}	-	47.3 89.5 84.0 78.5	-	mJ
Thermal Resistance, Junction to Case	Per FRD		R _{thJC}	-	0.064	-	K/W
Thermal Resistance, Case to Heatsink	Per FRD $\lambda_{grease} = 1W/(m \cdot K)$		R _{thCH}	-	0.038	-	K/W
Temperature under Switching Conditions ²⁾			T _{vj op}	-40	-	175	°C

NTC-Thermistor / NTC Characteristic Values

				min.	typ.	max.	
Rated Resistance	T _{NTC} = 25°C		R ₂₅	-	5	-	KΩ
Deviation of R100 R100	T _{NTC} = 100°C, R ₁₀₀ = 491Ω		ΔR/R	-5	-	5	%
Power Dissipation	T _{NTC} = 25°C		P ₂₅	-	-	20	mW
B-Value B	R ₂ = R ₂₅ exp[B _{25/50} (1/T ₂ -1/(298.15K))]		B _{25/50}	-	3375	-	K
	R ₂ = R ₂₅ exp[B _{25/80} (1/T ₂ -1/(298.15K))]		B _{25/80}	-	3425	-	K
	R ₂ = R ₂₅ exp[B _{25/100} (1/T ₂ -1/(298.15K))]		B _{25/100}	-	3443	-	K

Module

Isolation Test Voltage	RMS, f=50Hz, t=3s	V _{ISOL}	3.4	kV
Isolation Test Voltage of NTC NTC	RMS, f=50Hz, t=3s	V _{ISOL(NTC)}	3.4	kV
Material of Module Baseplate			Cu	
Internal Isolation			ZTA	
Creepage Distance	Terminal to heatsink, min		>14.7	mm
	Terminal to terminal, min		>15.1	
Clearance	Terminal to heatsink, min		>9.6	mm
	Terminal to terminal, min		>12.5	
Comparative Tracking Index		CTI	>200 ³⁾	

min. typ. max.

Stray Inductance Module		L _{sCE}	-	20	-	nH
Module Lead Resistance, Terminals-Chip	T _C = 25°C, Per Switch	R _{CC'+EE'}	-	0.8	-	mΩ
Storage Temperature		T _{stg}	-40	-	125	°C
Mounting Torque for Module Mounting	Screw M5 / M5	M	4.0	-	5.0	Nm
Power terminal installation torque	Screw M6 / M6	M	4.0	-	5.0	Nm
Weight		G	-	345	-	g


1) Terminal impedance is not included.

2) T_{vj op} > 150°C is allowed for operation at overload conditions.


3) CTI is greater than 200

Circuit Diagram


Output characteristic IGBT, Inverter (typical)
 Inclusive RCC+EE'
 $I_c = f(V_{CE}), V_{GE} = 15V$




Output characteristic IGBT, Inverter (typical)
 Inclusive RCC+EE'
 $I_c = f(V_{CE}), T_j = 175^\circ C$



Transfer characteristic IGBT, Inverter (typical),
 Inclusive RCC+EE'
 $I_c = f(V_{GE}), V_{CE} = 20V$




Gate Charge characteristic IGBT, Inverter
 $V_{GE} = f(Q_g)$
 $I_c = 600A, T_j = 25^\circ C$




Switching losses IGBT, Inverter(typical)

$E = f(I_c)$, $V_{GE} = +15V$, $R_{Gon} = 1\Omega$, $R_{Goff} = 1\Omega$, $V_{CE} = 900V$




Switching losses IGBT, Inverter(typical)

$E = f(R_G)$, $V_{GE} = +15V$, $I_c = 600A$, $V_{CE} = 900V$




Switching times IGBT, Inverter (typical)

$t = f(I_c)$, $V_{GE} = \pm 15V$, $V_{CE} = 900V$, $T_j = 175^\circ C$
 $R_{Gon} = 1\Omega$, $R_{Goff} = 1\Omega$




Switching times IGBT, Inverter (typical)


$t = f(R_G)$, $V_{GE} = \pm 15V$, $V_{CE} = 900V$, $T_j = 175^\circ C$
 $I_c = 600A$




Transient thermal impedance IGBT, Inverter
 $Z_{thJC}=f(t)$




Reverse bias safe operating area IGBT,
 Inverter(RBSOA)
 $I_C = f(V_{CE}), V_{GE} = +15V, R_{Goff} = 1\Omega, T_j = 175^\circ C$



Forward characteristic FRD, Inverter(typical),
 Inclusive RCC+EE'
 $I_F = f(V_F)$




Switching Losses FRD, Inverter (typical),
 $E_{rec} = f(I_F), R_{Gon} = 1\Omega, V_{CE} = 900V$




Switching Losses FRD, Inverter (typical),

$E_{rec} = f(R_g)$, $I_c = 600A$, $V_{CE} = 900V$



Transient thermal impedance FRD, Inverter


FRD
 $Z_{thJC} = f(t)$




NTC Thermistor temperature characteristic

(typical)


$R = f(T)$



Package Dimension/
Dimensions in Millimeters



Internal Circuit



Terms and Conditions of Usage of Technicon products

The data contained in this product datasheet is exclusively intended for technically trained staff. You and your technical departments will have to evaluate the suitability of the product for the intended application and the completeness of the product data with respect to such application. This product data sheet is describing the characteristics of this product for which a warranty is granted. Any such warranty is granted exclusively pursuant to the terms and conditions of the supply agreement. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary.

The user of Technicon products is responsible for the safety of their applications embedding Technicon products and must take adequate safety measures to prevent the applications from causing physical injury, fire, or other problems if any of Technicon products become faulty. The user is responsible for ensuring that the application design is compliant with all applicable laws, regulations, norms, and standards.

Except as otherwise explicitly approved by Technicon in a written document signed by authorized representatives of Technicon, Technicon products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.

No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. Technicon does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets, or other intellectual property rights, nor the rights of others.

Technicon makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. This document supersedes and replaces all information previously supplied and may be superseded by updates. Technicon reserves the right to make changes.

For any questions or suggestions, please contact us at info@technicon.asia .